

BP40



Large-Diaphragm Dynamic Broadcast Microphone

broadcast & production microphones



Features

- Rich, natural condenser-like sound
- Large diameter diaphragm with patented floating-edge construction for optimal performance
- Humbucking coil prevents electromagnetic interference (EMI)
- Optimized capsule placement for commanding vocal presence even at a distance
- Hypercardioid polar pattern provides maximum feedback rejection and isolation of desired sound source
- Switchable 100 Hz high-pass filter
- Multistage windscreen provides superior internal pop filtering
- Rugged, all-metal construction for dependable use in professional broadcast environments

Description

The BP40 is a large-diaphragm dynamic microphone with a hypercardioid polar pattern. It is designed for use as a broadcast vocal microphone.

The hypercardioid polar pattern of the microphone is more sensitive to sound originating directly in front of the element, making it useful for controlling feedback and reducing pickup of unwanted sounds.

The output of the microphone is a 3-pin XLRM-type connector.

The microphone is equipped with a switch that permits choice of flat response or low-frequency roll-off (via integral 100 Hz high-pass filter).

The microphone is enclosed in a rugged housing with a multistage windscreen. The capsule is set back from the screen to provide a more consistent response. The included AT8483 mounting clamp fits any microphone stand with 5/8"-27 threads. For improved protection from noise, shock and vibration, the AT8484 shock mount, available separately, may be used in place of the mounting clamp; it likewise fits stands with 5/8"-27 threads. A soft protective pouch is also included.

Operation and Maintenance

Output is low impedance (Lo-Z) balanced. The signal appears across Pins 2 and 3; Pin 1 is ground (shield). Output phase is "Pin 2 hot"—positive acoustic pressure produces positive voltage at Pin 2.

To avoid phase cancellation and poor sound, all mic cables must be wired consistently: Pin 1-to-Pin 1, etc.

An integral 100 Hz high-pass filter provides easy switching from a flat frequency response to a low-end roll-off. The roll-off position reduces the pickup of low-frequency ambient noise (such as traffic, air-handling

systems, etc.), room reverberation and mechanically coupled vibrations. To engage the filter slide the switch toward the "bent" line.

Take care to keep foreign particles from entering the windscreen. An accumulation of iron or steel filings on the diaphragm, and/or foreign material in the windscreen's mesh surface, can degrade performance.

To reduce the environmental impact of a multi-language printed document, product information is available online at www.audio-technica.com in a selection of languages.

Afin de réduire l'impact sur l'environnement de l'impression de plusieurs langues, les informations concernant les produits sont disponibles sur le site www.audio-technica.com dans une large sélection de langue.

Para reducir el impacto al medioambiente, y reducir la producción de documentos en varios leguajes, información de nuestros productos están disponibles en nuestra página del Internet: www.audio-technica.com.

Para reduzir o impacto ecológico de um documento impresso de várias linguas, a Audio-Technica providência as informações dos seus produtos em diversas linguas na www.audio-technica.com.

Per evitare l'impatto ambientale che la stampa di questo documento determinerebbe, le informazioni sui prodotti sono disponibili online in diverse lingue sul sito www.audio-technica.com.

Der Umwelt zuliebe finden Sie die Produktinformationen in deutscher Sprache und weiteren Sprachen auf unserer Homepage: www.audio-technica.com.

Om de gevolgen van een gedrukte meertalige handleiding op het milieu te verkleinen, is productinformatie in verschillende talen "on-line" beschikbaar op: www.audio-technica.com.

本公司基於減少對環境的影響，將不作多語言文件的印刷，有關產品訊息可在 www.audio-technica.com 的官方網頁上選擇所屬語言及瀏覽。

本公司基于减少对环境的影响，将不作多语言文档的印刷，有关产品信息可在 www.audio-technica.com 的官方网页上选择所属语言和浏览。

자원 절약, 환경보호를 위해 국문 사용 설명서는 인쇄하지 않았습니다. 제품정보는 www.audio-technica.com 에서 원하는 언어 선택 후에 다운로드 받으실 수 있습니다.

Specifications

Element	Dynamic
Polar pattern	Hypercardioid
Frequency response	50-16,000 Hz
Low frequency roll-off	100 Hz, 6 dB/octave
Open circuit sensitivity	-48 dB (3.9 mV) re 1V at 1 Pa
Impedance	450 ohms
Switch	Flat, roll-off
Weight	632 g (22.3 oz) without AT8483
Dimensions	164.0 mm (6.45") long, 56.0 mm (2.20") diameter
Output connector	Integral 3-pin XLRM-type
Audio-Technica case style	R12
Accessories furnished	AT8483 mounting clamp for 5/8"-27 threaded stands; 5/8"-27 to 3/8"-16 threaded adapter; soft protective pouch

In the interest of standards development, A.T.U.S. offers full details on its test methods to other industry professionals on request.



1 Pascal = 10 dynes/cm² = 10 microbars = 94 dB SPL

Specifications are subject to change without notice.



frequency response: 50–16,000 Hz

polar pattern



Audio-Technica Corporation
audio-technica.com ©2015 Audio-Technica